

LONG KE DEFENSE

LKD. 40D SPECIFICATION

Model Number Φ 40.0mm	Maximum Allowable Voltage		Varistor Voltage		Clamping voltage (max.)		Rated voltage reference (V)	Maximum Peak Current (8/20μs)		Maximum Energy (Joule) 10/1000 μs	Typical Capacitance (Reference) @ 1KHz (pf)
	AC. Rms (V)	DC (V)	V1.0mA (V)		VC (V)	IP (A)		In. 10 times (KA)	I Max.		
			min.	max.							
40D201K	130	170	185	225	340	250	AC 125	20	45	400	7500
40D221K	140	180	198	242	360	250				450	6750
40D241K	150	200	216	264	395	250				480	6185
40D271K	175	225	243	297	455	250				540	5625
40D301K	190	250	270	330	500	250				600	4875
40D331K	210	275	297	363	550	250	AC 250			655	4500
40D361K	230	300	324	396	595	250	Telephone test			745	4125
40D391K	250	320	351	429	650	250				830	3750
40D431K	275	350	387	473	710	250	AC 250			920	3485
40D471K	300	385	423	517	775	250				1000	3185
40D511K	320	415	459	561	845	250				1060	2925
40D561K	350	460	504	616	925	250				1150	2660
40D621K	385	505	558	682	1025	250				1250	2435
40D681K	420	560	612	748	1120	250				1250	2250
40D711K	440	585	644	786	1180	250				1260	2115
40D751K	460	615	675	825	1240	250				1280	2000
40D781K	485	640	702	858	1290	250				1350	1915
40D821K	510	670	738	902	1355	250				1395	1875
40D911K	550	745	819	1001	1500	250	AC 380 or G			1475	1650
40D951K	575	765	855	1045	1570	250				1485	1575
40D102K	625	825	900	1100	1650	250		1550	1500		
40D112K	680	895	990	1210	1815	250		1700	1350		
40D122KA	750	990	1080	1320	1980	250		1750	1200		