

LONG KE Defense

LKD 34S. Specification

Model Number	Maximum Allowable Voltage		Varistor Voltage		Clamping voltage (max.)		Rated voltage reference (V)	8/20us Peak Current		Maximum Energy (Joule) 10/1000 us	Typical Capacitance (Reference) (@ 1KHz) (pf)			
	AC.Rms (V)	DC (V)	V1.0mA(V) min. max.		VC (V)	IP (A)		In. 10times (KA)	I Max.					
34S470K	30	38	42	52	93	60	DC 24	10	20	96	35000			
34S560K	35	45	50	63	110	60				115	29500			
34S680K	40	56	61	75	135	60				136	24200			
34S820K	50	65	74	90	135	300	DC 48	20	50	156	17950			
34S101K	60	85	90	110	165	300	DC 60			195	15000			
34S121K	75	100	108	132	200	300				235	12200			
34S151K	95	125	135	165	250	300				296	10000			
34S181K	115	150	162	198	300	300	AC 100			350	8250			
34S201K	130	170	185	225	340	300	AC 125			400	6750			
34S221K	140	180	198	242	360	300				450	6400			
34S241K	150	200	222	270	395	300				480	5650			
34S271K	180	225	256	310	455	300				540	5100			
34S301K	190	250	270	330	500	300	AC 250			600	4510			
34S331K	210	275	297	363	550	300		656	4150					
34S361K	230	300	324	396	595	300	Telephone test	745	3750					
34S391K	250	320	362	440	650	300	AC 250	20	50	830	3500			
34S431K	275	350	387	473	710	300				920	2950			
34S471K	300	385	423	517	775	300				1000	2880			
34S511K	320	415	459	561	845	300				1060	2650			
34S561K	350	460	504	616	925	300				1150	2450			
34S621K	385	505	558	682	1025	300				1250	2200			
34S681K	420	560	612	748	1120	300				1250	2000			
34S711K	440	585	644	786	1180	300				1280	1950			
34S751K	460	615	675	825	1240	300				AC 380 or G	20	45	1280	1820
34S781K	485	640	702	858	1290	300							1350	1750
34S821K	510	670	738	902	1355	300	1395	1650						
34S911K	550	745	819	1001	1500	300	1475	1500						
34S951K	575	760	855	1045	1570	300	1485	1430						
34S102K	625	825	900	1100	1650	300	1550	1350						
34S112K	680	895	990	1210	1815	300	1700	1230						
34S122K	750	980	1150	1320	1980	300	1750	1135						
34S142K	850	1120	1315	1540	2310	300	15	40	1750				970	
34S162K	1000	1320	1550	1760	2640	300			2000				840	
34S182K	1100	1485	1700	1980	2970	300			2000	800				