

LONG KE Defense

LKD . 33P__KASD1 Specification

Model Number	Maximum Allowable Voltage		Varistor Voltage		Clamping voltage (max.)		Rated voltage	Maximum peak current (8/20us)		Maximum Energy (Joule)	Typical Capacitance (Reference)
	AC. Rms (V)	DC (V)	V1.0mA (V)		VC (V)	IP (A)		In (V)	I max (KA)		
Normal			min.	max.						10/1000 μs	@ 1KHz (pf)
33P331KASD1	210	275	297	363	550	300	AC 250 Telephone test	20	50	656	4150
33P361KASD1	230	300	324	396	595	300				745	3750
33P391KASD1	250	320	371	449	650	300				830	3500
33P431KASD1	275	350	410	496	710	300	920			2950	
33P471KASD1	300	385	423	517	775	300	1000			2880	
33P511KASD1	320	415	459	561	845	300	1060			2650	
33P561KASD1	350	460	504	616	925	300	1150		2450		
33P621KASD1	385	505	558	682	1025	300	1250		2200		
33P681KASD1	420	560	612	748	1120	300	1250		2000		
33P711KASD1	440	575	644	786	1180	300	1265		1910		
33P751KASD1	460	615	675	825	1240	300	45		1280	1820	
33P781KASD1	485	640	702	858	1290	300			1350	1750	
33P821KASD1	510	670	738	902	1355	300		1395	1650		
33P911KASD1	550	745	819	1001	1500	300	AC 380 or G	1475	1500		